

Multifunctional Touch Panel PC

# K750 SERIES

K750 series is Flytech's industrial Panel PC with multiple touchscreen sizes and rich peripherals integrated that suits an array of applications. With durable die-casting housing, powerful performance, full I/O port support and flexible mounting options, making it perfect for retail, hospitality, medical and industrial uses.





SPECIFICATIONS

<b>System</b>	Motherboard	D36	D86U	D87U
	Processor	K755, K757, K758, K759: Intel® Bay Trail J1900	K755, K757, K758, K759: Intel® Skylake U 3955U/i3-6100U/i5-6300U	K757, K758, K759: Intel® Skylake U 3955U/i5-6300U
	Memory	1x DDR3 up to 8GB	1x DDR3 up to 8GB	2x DDR4 up to 32GB
	Storage	1x 2.5" SATA SSD up to 512GB	1x 2.5" SATA SSD up to 512GB	1x 2.5" SATA SSD up to 512GB
	TPM	-	-	TPM 2.0
	Supported OS	Windows 10 IoT Enterprise, Linux	Windows 10 IoT Enterprise, Linux	Windows 10 IoT Enterprise, Linux
<b>Expansion</b>	Expansion module	1x Mini PCI-E Socket	1x Mini PCI-E Socket	1x Mini PCI-E Socket 1x M.2 Socket
	Size and Resolution	K755: 10.1" 1920 x 1200 K757: 15.6" 1366 x 768 K758: 18.5" 1366 x 768 K759: 21.5" 1920 x 1080	K755: 10.1" 1920 x 1200 K757: 15.6" 1366 x 768 K758: 18.5" 1366 x 768 K759: 21.5" 1920 x 1080	K757: 15.6" 1366 x 768 K758: 18.5" 1366 x 768 K759: 21.5" 1920 x 1080
<b>Display</b>	Touch Screen	True-Flat PCAP multi-touch	True-Flat PCAP multi-touch	True-Flat PCAP multi-touch
	USB	K755: 1x USB3.0, 3x USB2.0 K757, K758, K759: 1x USB3.0, 4x USB2.0	K755: 2x USB3.0, 3x USB2.0 K757, K758, K759: 4x USB3.0, 2x USB2.0	K757, K758, K759: 4x USB3.0
<b>I/O ports</b>	Serial Port	K755: 3x RJ48 K757, K758, K759: 4x RJ48	K755: 3x RJ48 K757, K758, K759: 4x RJ48	K757, K758, K759: 2x RJ48
	LAN	K755: 1x RJ45 K757, K758, K759: 2x RJ45	K755: 1x RJ45 K757, K758, K759: 2x RJ45	K757, K758, K759: 2x RJ45
	Audio Jack	K757, K758, K759: 1x Line-out, 1x Mic-in	K757, K758, K759: 1x Line-out, 1x Mic-in	K757, K758, K759: 1x Line-out, 1x Mic-in
	VGA	1x DB15	1x DB15	-
	HDMI	-	-	1x HDMI
	DVI	K757, K758, K759: 1x DVI-D (option)	K757, K758, K759: 1x DVI-D (option)	-
	DC Jack	1x 4PIN (with latch)	1x 4PIN (with latch)	1x 4PIN (with latch)
	<b>Audio</b>	Speaker	2x 2W	2x 2W
<b>Power</b>	Power Supply	K755, K757, K758: 65W / 19V K759: 90W / 19.5 V	K755, K757, K758: 65W / 19V K759: 90W / 19.5V	90W / 19-19.5V
	EMC & Safety	FCC Class A, CE Mark Class A, LVD	FCC Class A, CE Mark Class A, LVD	FCC Class B, CE Mark Class B, LVD
<b>Certificate</b>	Medical	-	-	EN 60601-1, EN 60601-1-2, ANSI / AAMI ES60601-1
	Dust & Water Proof	Front IP65	Front IP65	Front IP65
<b>Environment</b>	Ventilation	Fanless	Fanless	Fanless
	Operating Temperature	0°C ~ 35°C (32°F ~ 95°F)	0°C ~ 35°C (32°F ~ 95°F)	0°C ~ 35°C (32°F ~ 95°F)
	Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)	-20°C ~ 60°C (-4°F ~ 140°F)	-20°C ~ 60°C (-4°F ~ 140°F)
	Humidity	20% ~ 85% RH non-condensing	20% ~ 85% RH non-condensing	20% ~ 85% RH non-condensing
	<b>Dimensions</b>	Dimensions (WxDxH)	K755: 262 x 38 x 170 mm (10.4" x 1.5" x 6.7")	K755: 262 x 38 x 170 mm (10.4" x 1.5" x 6.7")
K757: 396 x 48 x 245 mm (15.6" x 1.9" x 9.6")			K757: 396 x 48 x 245 mm (15.6" x 1.9" x 9.6")	K757: 396 x 48 x 245 mm (15.6" x 1.9" x 9.6")
K758: 464 x 48 x 284 mm (18.3" x 1.9" x 11.2")			K758: 464 x 48 x 284 mm (18.3" x 1.9" x 11.2")	K758: 464 x 48 x 284 mm (18.3" x 1.9" x 11.2")
K759: 536 x 48 x 328 mm (21.1" x 1.9" x 12.9")			K759: 536 x 48 x 328 mm (21.1" x 1.9" x 12.9")	K759: 536 x 48 x 328 mm (21.1" x 1.9" x 12.9")
<b>Weight</b>	Weight	K755: 1.5 kg (3.3 lbs)	K755: 1.5 kg (3.3 lbs)	
		K757: 4.5 kg (9.9 lbs)	K757: 4.5 kg (9.9 lbs)	K757: 4.5 kg (9.9 lbs)
		K758: 6.8 kg (15 lbs)	K758: 6.8 kg (15 lbs)	K758: 6.8 kg (15 lbs)
		K759: 8 kg (17.6 lbs)	K759: 8 kg (17.6 lbs)	K759: 8 kg (17.6 lbs)
<b>Mounting</b>	VESA Mount	75 x 75	75 x 75	75 x 75
	Wireless LAN + BT	802.11b/g/n WLAN Card + BT4.0	802.11b/g/n WLAN Card + BT4.0	802.11b/g/n WLAN Card + BT4.0
<b>Options</b>	Webcam	2MP (Built-in)	2MP (Built-in)	2MP (Built-in)
	MSR	3-Track MSR	3-Track MSR	3-Track MSR
	Smart IC Card Reader, RFID,	Smart IC Card Reader, RFID,	Smart IC Card Reader, RFID,	Smart IC Card Reader, RFID,
	Device Box	2D Scanner, Line-out, Mic-in	2D Scanner, Line-out, Mic-in	2D Scanner, Line-out, Mic-in

※ PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE ※

Taiwan - Headquarters

No.168, Sing-ai Rd., Neihu District,  
Taipei City 11494, Taiwan, R.O.C.  
886-2-8791-4988  
886-2-8791-4966  
sales@flytech.com.tw  
www.flytech.com

U.S.A. - California

271 East Brokaw Road, San Jose,  
CA 95112, U.S.A.  
1-510-257-5180  
1-510-257-5181  
sales@flytech.com

China - Shanghai

3F Building 39, No. 333 Qin Jiang Rd.,  
Shanghai 200233, P.R.China  
86-21-5426-1555  
86-21-5426-1001  
sales@flytech.com.cn  
www.flytech.com.cn

China - Hong Kong SAR

Rm01, 6/F, Blk A, Tonic Industrial Centre,  
26 Kai Cheung Road, Kowloon Bay,  
Kowloon, Hong Kong.  
852-3525-5800  
852-2751-7447  
sales@flytech.com.hk

