

FLYTECH

POS5000

Flytech's POS 5000 is a powerful embedded Box PC built from SECC metal and equipped with a powerful Intel Skylake S processor and Rich I/O ports for a full range of peripheral connectivity. A sleek front key-lock door and side ventilation provide added security and optimal airflow. The POS 5000 offers modularized I/O boards, HDD, and Optional I/O boards for easy maintenance and upgrade. Easy access to the motherboard and HDD for serviceability. It supports AMT/vPro for remote management functionality and RAID technology for data loss prevention. The POS 5000 is an excellent embedded Box PC solution for any type of business application.





APPLICATION BENEFITS

- Easy Maintenance
- Smart Connectivity
- Outstanding Performance
- Multipurpose Embedded Box PC
- RAID Technology for Data Loss Prevention

FEATURES

- Intel Skylake S Processor
- SECC Metal Housing
- Front I/O for Easy Service
- Modular I/O Board Design for Easy Maintenance

- Superior Tool-less Design and Less Internal Cable
- Rich I/O Ports for Various Peripherals
- Dual HDD and RAID Technology for Transactions Data Back-up



SPECIFICATIONS

System	Motherboard Processor Graphic Engine Chipset Memory Storage	D89S Intel® Skylake S CPU Intel® HD Graphics DX12 Q170 2x DDR4 2133MHz SO-DIMM (max. 32GB) (dual channel) 2x 2.5" SATA HDD or SSD or SSD Module
Expansion	PCI-E Slot	2x Riser Card (1x PCI-E x1 slot, 1x PCI-E x16 slot)
External I/O Ports (Front Side)	USB Power Button Power LED Indicator HDD LED Indicator	1x USB3.0, 1x USB Type C 1 1 1
External I/O Ports (Rear Side)	USB Serial Port LAN Cash Drawer VGA Display Port Audio Line-out Audio Mic-in Powered USB	2x USB3.0, 2x USB2.0 3x DB9 (COM1/2 powered RS232, COM3 powered RS232/422/485) (default 0V; 0V/5V/12V enabled by BIOS setting) 1x RJ45 1x RJ11 (default 24V, 12V/24V) 1x DB15 (default 0V, 0V/12V) 2 1 1 2x Powered USB 12V, 1x Powered USB 24V
Option	COM4/ COM5/ DC-12V out Parallel Port PS/2	1 (2 x DB9, 1x 12V Power Output) 1 1
Power	Power Supply	Internal ATX 250W
Communication	Wireless LAN	802.11 series & antenna (Option)
Certificate	EMC & Safety	FCC Class B, CE Mark, LVD
Environment	Operating Temperature Storage Temperature Humidity	5°C ~ 35°C (41°F ~ 95°F) -20°C ~ 55°C (-4°F ~ 131°F) 20% ~ 85% RH non-condensing
Dimensions	W x D x H	263 x 299 x 132 mm (10.4" x 11.8" x 5.2")
Weight		6.5 kg (14.3 lbs)
OS Supported		Windows 7, POSReady 7, Windows 8.1, Windows Embedded 8.1 Industry, Windows 10 Windows 10 IoT Enterprise, Linux

※ PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE ※

Taiwan - Headquarters

No.168, Sing-ai Rd., Neihu District,
Taipei City 11494, Taiwan, R.O.C.
886-2-8791-4988
886-2-8791-4966
sales@flytech.com.tw
www.flytech.com

U.S.A. - California

271 East Brokaw Road, San Jose,
CA 95112, U.S.A.
1-510-257-5180
1-510-257-5181
sales@flytech.com

China - Shanghai

3F Building 39, No. 333 Qin Jiang Rd.,
Shanghai 200233, P.R.China
86-21-5426-1555
86-21-5426-1001
sales@flytech.com.cn
www.flytech.com.cn

China - Hong Kong SAR

Rm01, 6/F, Blk A, Tonic Industrial Centre,
26 Kai Cheung Road, Kowloon Bay,
Kowloon, Hong Kong.
852-3525-5800
852-2751-7447
sales@flytech.com.hk

